

TABLE 151-11
Typical Pier and Wharf Widths

Function Classification	Vessel Type	Minimum Pier Width (Feet)	Minimum Wharf Apron Width (Feet)	Railroad Tracks (Standard Gage)	Rail-mounted Cranes
1. Ammunition	Ammunition	100	100	-	-
2. Berthing	Aircraft Carrier	100*	-	-	-
3. Berthing	Cruiser	80	-	-	-
	Destroyer	80	-	-	-
	Frigate	80	-	-	-
	Submarine	60	-	-	-
	Auxiliary	80	-	-	-
4. Fitting-Out	Destroyer	100	-	2 Tracks 1 Each Side	2 30 ft. Gage, 1 Each Side
5. Repair	Cruiser	125	-	4 Tracks, 2 Each Side	2 30 ft. Gage, 1 Each Side
	Auxiliary	125	-	4 Tracks, 2 Each Side	2 30 ft. Gage, 1 Each Side
6. Fueling	Auxiliary	50	-	-	-
7. Supply (General Cargo)	Auxiliary	125 plus shed width	60	2 Tracks	-
8. Supply (Container Cargo)	Auxiliary	80	80	Up to 3 Tracks	1 50 ft. Gage

*Width applies when 60 foot camels are used to breast out carriers.